

Company Name: _____

Company Number: _____

**2023 MATE ROV COMPETITION. Diving In to Inspire Solutions Because Together Opportunity Runs Deep
NAVIGATOR CLASS SAFETY INSPECTION CHECKLIST**

Companies must bring this check list, the ROV, tether, surface controls, and any other item used in the deployment and operation of the ROV; they will all be inspected as part of the safety check. In addition, the SID, must be made available to the Safety Inspectors during the inspection process.

1.0 Initial Safety Inspection

Fluid power approved? Fluid power used? If yes to both, see Section 4.0 Pneumatics / Hydraulics
Laser approved? Laser used? If yes to both, see attached laser safety inspection sheet.

2.0 ROV Physical

All items attached to ROV are secure.
Hazardous items are identified and protection provided.
ALL propellers are completely shrouded or are enclosed inside the frame of the ROV.
No sharp edges or elements of the ROV design that could cause injury to personnel or damage the pool surface.

3.0 ROV Electrical

Tether is properly secured at the ROV.
No exposed motors. Brushless motors are considered exposed unless electrically sealed after purchase. Companies should provide proof of sealing procedure.
No exposed copper or bare wire.
All wiring securely fastened and properly sealed.*
Any splices in tether are properly sealed.*

3.1 Surface Controls Electrical & Physical

Single attachment point to the power source.
Anderson powerpole attachment to power source.
15 amp (or less) single inline fuse within 30 cm of power supply attachment point.
The surface control station is built in a neat and workmanship like manner. No loose components or unsecured wires. All electrical components are covered inside an enclosure.
No exposed copper or bare wire.
if used, 120VAC wiring is separated from the DC wiring.
If used, 120VAC wiring must be clearly identified from the DC and control voltages with signage and/or wire color schemes. If the color scheme is used, a key must be provided for identification.
All wires entering and leaving the surface control station must have adequate strain relief and wire abrasion protection as the wires pass through the enclosure.
Cameras operate off the MATE 12VDC power supply through the single attachment point to the power source.

* Properly sealed means that the wires cannot be exposed to water. Tape only sealing will allow the conduction of electricity through water.

At minimum, joints must be soldered, sealed with a proper waterproof sealant, and covered in tape or shrink wrap. For in water taping, silicone self-vulcanizing tape is preferred over thermoplastic tape. Cables with exposed male connections on both ends are not allowed.

4.0. Pneumatic / Hydraulic (if applicable)

Passed fluid power quiz.
Pneumatic or hydraulic diagram (SID) present.
Water is used as the hydraulic fluid.
All pressure lines have a minimum pressure rating of 100 PSI (pneumatic) or 300 PSI (hydraulic) stamped on the line or verified with specifications.
Valves meet the minimum pressure rating of 100 PSI (pneumatic) or 300 PSI (hydraulic)
Attachment to the pressure source is secure.
Pressure is regulated to: 40 PSI max for pneumatics 150 PSI max for hydraulics
Pressure vessels have a stamped pressure rating or verification by inspection.
Pressure vessels have a a current inspection sticker.
Pressure vessels can be secured on the pool deck.
Company fabricated pressure accumulator test results are provided (if used).
No hydraulic fluids are leaking.
Pneumatics utilize compressed air or inert gas.

SAFETY INSPECTION #1 PASSED: 10 POINTS

Failed: Items to correct noted on rear of this sheet.

SAFETY INSPECTION #2 PASSED: 10 POINTS

Failed: Items to correct noted on rear of this sheet.

SAFETY INSPECTION #3 PASSED: 10 POINTS

Failed: Reason / details are noted on rear of this sheet.

Total Safety Points:

On Site Inspection

0 or 10 points

--

Inspection #1: Items to address

Judge: _____

Inspection #2: Items to address

Judge: _____

Inspection #3: Reason

Judge: _____
