PIONEER CLASS SCORE SHEET

Company CEO:	Company Name		
Product demonstration station officials:			
Safety			
Check here if the company has their PASSED safety inspection c Companies without their safety inspection PASSED card cannot participate in the product demon			
Check here if tamper seal on fuse is still intact Companies with a broken tamper seal on their fuse must see the safety inspectors before their Re	OV enters the water.		
Check here if the company presented you with a JSA (Jobsite Sa	fety Analysis)		
Check here if vehicle (and float) matches photo taken at safety in Companies must use the same vehicle, float, and other devices that went through the safety insp			

Organizational and Operational Effectiveness (up to 10 points)	Poi	Points	
Up to 4 points - Teamwork/Collaboration & Communication			
Chain of command evident	0	1	
Roles clear and executed well	0	1	
Composure under pressure	0	1	
Supportive of each other and communicate well with each other	0	1	
Up to 2 points - Project Management			
Task plan is well thought out to maximize score	0	1	
Alternate plans available and all team members are aware of the plan	0	1	
Up to 2 points - Problem Solving & Ability to Deal with Obstacles			
Awareness of time	0	1	
Adjusting timeline to adapt to situations	0	1	
Up to 2 points - System Design & Control/Electrical			
ROV deployed by the end of the 5-minute set-up period	0	1	
ROV is under control of pilot and prepared to perform tasks	0	1	

Total Organizational and Operational Effectiveness (out of 10)

Bonus points for weight	Points	
Weight bonus (up to 10 points)	0 5 10	
ROV is less than 18 kg – 10 bonus points		
ROV is between 18.01 kg and 25 kg – 5 bonus points	Judge initials:	
ROV is between 25.01 kg and 35 kg – 0 bonus points		Total
Vehicles heavier than 35 kg may not compete	CEO initials:	

Fuses: ROV systems are allowed one replacement fuse during the product demonstration. In the event that the ROV system blows the second fuse during the demonstration, time will stop, the demonstration run will be over, and no additional points will be earned. Companies should have adequate replacement fuses on hand, MATE will not provide replacements.

2024: Observing Our Oceans: Understanding Our World and Creating Our Future

PIONEER CLASS SCORE SHEET

Task # 1: OOI: Coastal Pioneer Array (up to 50 points)		Points	
L. 1 up to 50 points – Release the multi-function node			
10 points – "trigger" the release of the multi-function node	0	10	
5 points – visually determine that the recovery has failed	0	5	
10 points – pull a pin to release the failed recovery float to the surface	0	10	
5 points – return the failed recovery float to the surface, side of the pool	0	5	
20 points – connect a recovery line to the bale on the multi-function node for manual recovery	0	20	

Total Task # 1 (out of 50)

Total

Task # 2: SMART Cables for Ocean Observing (up to 70 points)	Points		
2.1 up to 70 points – Deploy a SMART Cable			
up to 20 points – deploy SMART cable through three waypoints			
5 point each – deploy SMART cable through two waypoints located on the bottom of the seafloor	0	5	10
10 points – deploy SMART cable through a waypoint located on top of a seamount	0		10
10 points – place the SMART repeater in the designated location	0		10
5 points – return the ends of the cable to the surface, side of the pool	0		5
 up to 15 points – measure the temperature to check the SMART cable sensor readings 15 points – within 1 degree C 5 points – between 1.01 and 2 degrees C 	0	5	15
up to 20 points – connect the AUV docking station to the SMART cable repeater			
5 points – retrieve the power connector from the AUV docking station	0		5
15 points – install the power connector	0		15

Total Task # 2 (out of 70)

Total

Task # 3: From the Red Sea to Tennessee (up to 160 points)		Points	
3.1 up to 30 points – Probiotics 2			
10 points – place a probiotic irrigation system in the designated area	0	10	
10 points – deploy the probiotic sprinkler on the coral head	0	10	
10 points – activate the irrigation system	0	10	
3.2 up to 40 points – Coral Restoration			
10 points – transplant branching coral	0	10	
up to 30 points – transplant brain coral			
30 points – autonomously	0	10 30	
10 points – manually	0	10 50	
3.3 up to 40 points – 3D Coral modelling	1		
up to 40 points – via photogrammetry, autonomously create a scaled 3D model of the coral restoration area			
20 points – create a 3D model of the coral restoration area	0	20	
10 points – measure the length of the coral restoration area (within 5 cm)	0	10	
5 points – scale the 3D model using the length of the coral restoration area	0	5	
5 points – use the properly scaled 3D model to estimate the height of the coral restoration area (within 5 cm)	0	5	

	or		
up to 30 points – manually (0	CAD) create a scaled 3D model of the coral restoration	n area	
10 points – measure	e the length of the coral restoration area (within 5 cm)) 0	10
10 points – measure	e the height of the coral restoration area (within 5 cm)) 0	10
10 points – create a length and height m	scaled 3D model of the coral restoration area displayi easurements	ing the 0	10
	or		
up to 20 points – manually (prestoration area	paper) create a 3-view technical drawing of the coral		
5 points – measure f	the length of the coral restoration area (within 5 cm)	0	5
5 points – measure t	the height of the coral restoration area (within 5 cm)	0	5
•	technical drawing on paper of the coral restoration ar red length and height measurments with at least 3 vie		10
up to 50 points – Determine the	location of sturgeon spawning grounds		
10 points – recover an acous	tic receiver	0	10
up to 20 points – determine	the location of a potential spawning site		
15 points – create a	graph of sturgeon locations from the acoustic receive	er data 0	15
5 points – determine	e the potential spawning site	0	5
up to 20 points – characteriz	e the habitat at potential spawning site		
10 points – place an	ADCP	0	10
			10

Total Task # 3 (out of 160)

Total

1 up to 70 points - MATE Floats! 5 points - prior to the competition, building an operational vertical profiling float 5 points - deploy the float into the designated area 10 points - float communicates with the mission station prior to descending up to 50 points - float completes two vertical profiles Vertical Profile #1 10 points - float completes 1st vertical profile using a buoyancy engine or 5 points - float completes 1st profile not using a buoyancy engine 5 points - float communicates data to the mission station 10 points - data is graphed as depth over time Vertical Profile #2 10 points - float completes 2nd vertical profile using a buoyancy engine or 5 points - float completes 2nd vertical profile using a buoyancy engine or 5 points - float completes 2nd vertical profile using a buoyancy engine 0 points - float completes 2nd profile not using a buoyancy engine 0 points - float completes 2nd profile not using a buoyancy engine 0 points - float completes 2nd profile not using a buoyancy engine 0 points - float completes 2nd profile not using a buoyancy engine 0 points - float completes 2nd profile not using a buoyancy engine		Points	5
5 points – deploy the float into the designated area 10 points – float communicates with the mission station prior to descending up to 50 points – float completes two vertical profiles 10 points – float completes two vertical profiles Vertical Profile #1 10 points – float completes 1st vertical profile using a buoyancy engine or 5 points – float completes 1st profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time Vertical Profile #2 10 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd profile not using a buoyancy engine 5 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine 0 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine 0 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy e			
10 points – float communicates with the mission station prior to descending up to 50 points – float completes two vertical profiles Vertical Profile #1 10 points – float completes 1st vertical profile using a buoyancy engine or 5 points – float completes 1st profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time Vertical Profile #2 10 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – data is graphed as depth over time 0TE: If a company does not design and construct a float, or the float does not communicate at all onthe mission station, companies may graph MATE-provided data. The following replaces all pommunication and graphing points above.	0		5
up to 50 points – float completes two vertical profiles Vertical Profile #1 10 points – float completes 1st vertical profile using a buoyancy engine or 5 points – float completes 1st profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time Vertical Profile #2 10 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – data is graphed as depth over time 0TE: If a company does not design and construct a float, or the float does not communicate at all on the mission station, companies may graph MATE-provided data. The following replaces all pommunication and graphing points above.	0		5
Vertical Profile #1 10 points – float completes 1st vertical profile using a buoyancy engine or 5 points – float completes 1st profile not using a buoyancy engine 5 points – float completes 1st profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time Vertical Profile #2 10 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine 5 points – float completes 2nd profile not using a buoyancy engine 0 5 points – float completes 2nd profile not using a buoyancy engine 0 5 points – float completes 2nd profile not using a buoyancy engine 0 0 points – data is graphed as depth over time 0 0 points – data is graphed as depth over time 0 0TE: If a company does not design and construct a float, or the float does not communicate at all on the mission station, companies may graph MATE-provided data. The following replaces all pommunication and graphing points above.	0		10
10 points – float completes 1st vertical profile using a buoyancy engine or 5 points – float completes 1st profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time Vertical Profile #2 10 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – float completes 2nd profile not using a buoyancy engine 0 points – data is graphed as depth over time 0 points – data is graphed as depth over time 0 points – data is graphed as depth over time 0 points – data is graphed as depth over time 0 points – data is graphed as depth over time 0 points – data is graphed as depth over time 0 points – data is graphed as depth over time 0 points and graphing points above.			
or 5 points – float completes 1st profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time Vertical Profile #2 10 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd profile not using a buoyancy engine 5 points – float completes 2nd profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time OTE: If a company does not design and construct a float, or the float does not communicate at all othe mission station, companies may graph MATE-provided data. The following replaces all pommunication and graphing points above.			
5 points – float communicates data to the mission station 10 points – data is graphed as depth over time Vertical Profile #2 10 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd profile not using a buoyancy engine 5 points – float completes 2nd profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time OTE: If a company does not design and construct a float, or the float does not communicate at all othe mission station, companies may graph MATE-provided data. The following replaces all pommunication and graphing points above.	0	5	10
10 points – data is graphed as depth over time Vertical Profile #2 10 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd profile not using a buoyancy engine 5 points – float completes 2nd profile not using a buoyancy engine 10 points – data is graphed as depth over time OTE: If a company does not design and construct a float, or the float does not communicate at all othe mission station, companies may graph MATE-provided data. The following replaces all pommunication and graphing points above.			
Vertical Profile #2 10 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd profile not using a buoyancy engine 5 points – float completes 2nd profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time OTE: If a company does not design and construct a float, or the float does not communicate at all on the mission station, companies may graph MATE-provided data. The following replaces all pommunication and graphing points above.	0		5
10 points – float completes 2nd vertical profile using a buoyancy engine or 5 points – float completes 2nd profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time OTE: If a company does not design and construct a float, or the float does not communicate at all othe mission station, companies may graph MATE-provided data. The following replaces all pommunication and graphing points above.	0		10
or 5 points – float completes 2nd profile not using a buoyancy engine 5 points – float communicates data to the mission station 10 points – data is graphed as depth over time OTE: If a company does not design and construct a float, or the float does not communicate at all othe mission station, companies may graph MATE-provided data. The following replaces all ommunication and graphing points above.			
5 points – float communicates data to the mission station 10 points – data is graphed as depth over time OTE: If a company does not design and construct a float, or the float does not communicate at all o the mission station, companies may graph MATE-provided data. The following replaces all pommunication and graphing points above.	0	5	10
10 points – data is graphed as depth over time OTE: If a company does not design and construct a float, or the float does not communicate at all o the mission station, companies may graph MATE-provided data. The following replaces all ommunication and graphing points above.	0		
OTE: If a company does not design and construct a float, or the float does not communicate at all o the mission station, companies may graph MATE-provided data. The following replaces all ommunication and graphing points above.	0		5
the mission station, companies may graph MATE-provided data. The following replaces all ommunication and graphing points above.	0		10
10 points MATE provided data is used to graph donth over time			
10 points – MATE-provided data is used to graph depth over time	0		10
			out of 70)

Penalty Points (deduct 5 points for each infraction)	No. of Infractions
Safety: Product demonstration officials may deduct points for safety violations. Minor violations are a 5 point penalty. Major violations may be 10 or more points. Product demonstration officials may also disqualify a company for extreme safety violations. Note: An official's decision to disqualify a company due to safety concerns is final. If there is a safety concern, please contact the lead safety inspector or competition coordinator.	
Tether Pulling: Company members cannot pull on the tether to assist in moving or turning the vehicle. Judges should issue a warning for the first infraction and begin deducting points AFTER the first infraction.	а
Illegal communication : Company members at the side of the pool may not communicate visual evidence of the ROV status such as location of vehicle, need to turn, that the vehicle is stuck, etc.	Ь
Debris : Companies that leave debris (e.g. parts of their ROV, including weights and flotation) in the pool at the end of the product demonstration time, or leave debris that a diver must retrieve will receive penalty points. Product demonstration props are NOT considered debris. A company constructed collection basket is considered debris if it is still in the water, not under control of the ROV, when product demonstration time ends.	c
Diver Assistance: Any diver assistance (if available) must be requested by the company and will result in a 5 point penalty. The clock does not stop during diver assistance.	d
Total Penalty Points	(total a + b + c + d) plus safety violations
	X 5 =

TIME BONUS (1 point for every minute and 0.01 point for every second under 15 minutes)	
Duration of Product Demonstration:	
Minutes under 15 remaining:X 1 point =	
Seconds remaining: X 0.01 point =	Total
Time bonus	

	Grand Total
TOTAL PRODUCT DEMONSTRATION SCORE	

Official's initials: _____

Company CEO's initials: _____